

Pozicionér vidlíc bez samostatného bočného posuvu

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
PN 25.092	2500 kg/500 mm	63 kg	2	350/840 mm	920 mm	800 mm
PN 25.098	2500 kg/500 mm	66 kg	2	350/900 mm	980 mm	800 mm
PN 25.102	2500 kg/500 mm	69 kg	2	350/940 mm	1020 mm	800 mm
PN 25.104	2500 kg/500 mm	73 kg	2	350/960 mm	1040 mm	800 mm
PN 25.110	2500 kg/500 mm	74 kg	2	350/1020 mm	1100 mm	900 mm
PN 25.115	2500 kg/500 mm	75 kg	2	350/1070 mm	1150 mm	900 mm
PN 35.110	3500 kg/500 mm	102 kg	3	350/1020 mm	1100 mm	900 mm
PN 35.115	3500 kg/500 mm	107 kg	3	350/1070 mm	1150 mm	900 mm
PN 35.125	3500 kg/500 mm	122 kg	3	350/1170 mm	1250 mm	1000 mm
PN 50.115	5000 kg/500 mm	135 kg	3	380/1060 mm	1150 mm	900 mm
PN 50.125	5000 kg/500 mm	140 kg	3	380/1160 mm	1250 mm	1000 mm
PN 50.135	5000 kg/500 mm	145 kg	3	380/1260 mm	1350 mm	1000 mm

