

Pozicionér vidlíc so samostatným bočným posuvom

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
PN 25T.092	2500 kg/500 mm	74 kg	2	350/840 mm	920 mm	800 mm
PN 25T.098	2500 kg/500 mm	75 kg	2	350/900 mm	980 mm	800 mm
PN 25T.102	2500 kg/500 mm	77 kg	2	350/940 mm	1020 mm	800 mm
PN 25T.104	2500 kg/500 mm	78 kg	2	350/960 mm	1040 mm	800 mm
PN 25T.110	2500 kg/500 mm	81 kg	2	350/1020 mm	1100 mm	900 mm
PN 25T.115	2500 kg/500 mm	85 kg	2	350/1070 mm	1150 mm	900 mm
PN 35T.110	3500 kg/500 mm	113 kg	3	350/1020 mm	1100 mm	900 mm
PN 35T.115	3500 kg/500 mm	117 kg	3	350/1070 mm	1150 mm	900 mm
PN 35T.125	3500 kg/500 mm	123 kg	3	350/1170 mm	1250 mm	1000 mm
PN 50T.115	5000 kg/500 mm	150 kg	3	380/1060 mm	1150 mm	900 mm
PN 50T.125	5000 kg/500 mm	155 kg	3	380/1160 mm	1250 mm	1000 mm
PN 50T.135	5000 kg/500 mm	160 kg	3	380/1260 mm	1350 mm	1000 mm

