

Pozicionér vidlíc so samostatným bočným posuvom

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
PH 25T.092	2500 kg/500 mm	68 kg	2	360/850 mm	920 mm	800 mm
PH 25T.098	2500 kg/500 mm	71 kg	2	360/910 mm	980 mm	800 mm
PH 25T.102	2500 kg/500 mm	73 kg	2	360/950 mm	1020 mm	800 mm
PH 25T.104	2500 kg/500 mm	74 kg	2	360/970 mm	1040 mm	800 mm
PH 25T.110	2500 kg/500 mm	80 kg	2	360/1030 mm	1100 mm	800 mm
PH 25T.115	2500 kg/500 mm	82 kg	2	360/1080 mm	1150 mm	900 mm
PH 35T.110	3500 kg/500 mm	119 kg	3	360/1030 mm	1100 mm	900 mm
PH 35T.115	3500 kg/500 mm	123 kg	3	360/1080 mm	1150 mm	900 mm
PH 35T.125	3500 kg/500 mm	131 kg	3	360/1180 mm	1250 mm	1000 mm
PH 50T.115	5000 kg/500 mm	156 kg	3	410/1020 mm	1150 mm	900 mm
PH 50T.125	5000 kg/500 mm	165 kg	3	410/1220 mm	1350 mm	1100 mm
PH 50T.135	5000 kg/500 mm	175 kg	3	410/1220 mm	1350 mm	1100 mm
PH 55T.120	5500 kg/600 mm	233 kg	4	460/1050 mm	1200 mm	1100 mm
PH 55T.150	5500 kg/600 mm	273 kg	4	460/1350 mm	1500 mm	1300 mm
PH 55T.170	5500 kg/600 mm	303 kg	4	460/1550 mm	1700 mm	1500 mm
PH 70T.120	7000 kg/600 mm	262 kg	4	460/1050 mm	1200 mm	1100 mm
PH 70T.150	7000 kg/600 mm	297 kg	4	460/1350 mm	1500 mm	1350 mm
PH 70T.180	7000 kg/600 mm	343 kg	4	460/1550 mm	1700 mm	1600 mm
PH 70T.200	7000 kg/600 mm	389 kg	4	460/1850 mm	2000 mm	2000 mm
PH 70T.220	7000 kg/600 mm	404 kg	4	460/2050 mm	2200 mm	2200 mm
PH 80T.120	8000 kg/600 mm	267 kg	4	460/1050 mm	1200 mm	1100 mm
PH 80T.150	8000 kg/600 mm	302 kg	4	460/1350 mm	1500 mm	1350 mm
PH 80T.180	8000 kg/600 mm	349 kg	4	460/1550 mm	1800 mm	1600 mm
PH 80T.200	8000 kg/600 mm	396 kg	4	460/1850 mm	2000 mm	2000 mm
PH 80T.220	8000 kg/600 mm	414 kg	4	460/2050 mm	2200 mm	2200 mm

