

Pozicionér vidlíc s unášačom vidlíc so samostatným bočným posuvom

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
PL 25T.092	2500 kg/500 mm	112 kg	2	340/790 mm	920 mm	800 mm
PL 25T.098	2500 kg/500 mm	115 kg	2	340/850 mm	980 mm	800 mm
PL 25T.104	2500 kg/500 mm	120 kg	2	340/910 mm	1040 mm	800 mm
PL 25T.110	2500 kg/500 mm	122 kg	2	340/970 mm	1100 mm	900 mm
PL 25T.115	2500 kg/500 mm	123 kg	2	340/1020 mm	1150 mm	900 mm
PL 25T.125	2500 kg/500 mm	130 kg	2	340/1120 mm	1250 mm	950 mm
PL 25T.130	2500 kg/500 mm	138 kg	2	340/1170 mm	1300 mm	950 mm
PL 25T.135	2500 kg/500 mm	142 kg	2	340/1220 mm	1350 mm	1050 mm
PL 25T.140	2500 kg/500 mm	147 kg	2	340/1270 mm	1400 mm	1050 mm
PL 25T.145	2500 kg/500 mm	152 kg	2	340/1320 mm	1450 mm	1050 mm
PL 35T.110	3500 kg/500 mm	173 kg	2	380/960 mm	1100 mm	900 mm
PL 35T.115	3500 kg/500 mm	177 kg	3	380/1010 mm	1150 mm	900 mm
PL 35T.125	3500 kg/500 mm	188 kg	3	380/1110 mm	1250 mm	1000 mm
PL 35T.130	3500 kg/500 mm	190 kg	3	380/1160 mm	1300 mm	1000 mm
PL 35T.135	3500 kg/500 mm	194 kg	3	380/1210 mm	1350 mm	1000 mm
PL 35T.140	3500 kg/500 mm	198 kg	3	380/1260 mm	1400 mm	1100 mm
PL 35T.145	3500 kg/500 mm	202 kg	3	380/1310 mm	1450 mm	1100 mm
PL 35T.150	3500 kg/500 mm	206 kg	3	380/1360 mm	1500 mm	1150 mm
PL 50T.110	5000 kg/500 mm	184 kg	3	380/960 mm	1100 mm	900 mm
PL 50T.115	5000 kg/500 mm	191 kg	3	380/1010 mm	1150 mm	900 mm
PL 50T.125	5000 kg/500 mm	208 kg	3	380/1110 mm	1250 mm	1000 mm
PL 50T.130	5000 kg/500 mm	212 kg	3	380/1160 mm	1300 mm	1000 mm
PL 50T.135	5000 kg/500 mm	215 kg	3	380/1210 mm	1350 mm	1000 mm
PL 50T.140	5000 kg/500 mm	233 kg	3	380/1260 mm	1400 mm	1100 mm
PL 50T.145	5000 kg/500 mm	240 kg	3	380/1310 mm	1450 mm	1100 mm
PL 50T.150	5000 kg/500 mm	247 kg	3	380/1360 mm	1500 mm	1150 mm
PL 50T.155	5000 kg/500 mm	254 kg	3	380/1410 mm	1550 mm	1250 mm
PL 50T.160	5000 kg/500 mm	261 kg	3	380/1460 mm	1600 mm	1250 mm
PL 50T.165	5000 kg/500 mm	268 kg	3	380/1510 mm	1650 mm	1300 mm

