

# Pozicionér vidlíc s vidlicami na vodiacej tyči bez samostatného bočného posuvu

Označenie	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
PF 25.098	189 kg	2	300/910 mm	980 mm	800 mm
PF 25.104	193 kg	2	300/970 mm	1040 mm	800 mm
PF 25.110	237 kg	2	300/1030 mm	1100 mm	900 mm
PF 25.115	239 kg	2	300/1080 mm	1150 mm	900 mm
PF 25.125	245 kg	2	300/1180 mm	1250 mm	1000 mm
PF 25.130	247 kg	2	300/1230 mm	1300 mm	1000 mm
PF 25.150	258 kg	2	300/1430 mm	1500 mm	1100 mm
PF 50.110	375 kg	3	340/1040 mm	1100 mm	900 mm
PF 50.115	380 kg	3	340/1090 mm	1150 mm	900 mm
PF 50.125	390 kg	3	340/1190 mm	1250 mm	1000 mm
PF 50.135	400 kg	3	340/1290 mm	1350 mm	1000 mm
PF 50.155	419 kg	3	340/1490 mm	1550 mm	1200 mm
PF 50.165	429 kg	3	340/1590 mm	1650 mm	1200 mm
PF 60.150	639 kg	4	570/1420 mm	1500 mm	1200 mm
PF 60.170	679 kg	4	570/1620 mm	1700 mm	1400 mm
PF 60.190	719 kg	4	570/1720 mm	1800 mm	1500 mm
PF 80.180	757 kg	4	570/1720 mm	1800 mm	1500 mm
PF 80.200	797 kg	4	570/1920 mm	2000 mm	1600 mm
PF 80.220	837 kg	4	570/2120 mm	2200 mm	1800 mm
PF 120.220	1270 kg	4	670/2080 mm	2200 mm	1800 mm

