

Pozicionér vidlíc s vidlicami na vodiacej tyči so samostatným bočným posuvom

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
PF 25T.098	2500 kg/500 mm	190 kg	2	300/910 mm	980 mm	800 mm
PF 25T.104	2500 kg/500 mm	194 kg	2	300/970 mm	1040 mm	800 mm
PF 25T.110	2500 kg/500 mm	234 kg	2	300/1030 mm	1100 mm	900 mm
PF 25T.115	2500 kg/500 mm	236 kg	2	300/1080 mm	1150 mm	900 mm
PF 25T.125	2500 kg/500 mm	242 kg	2	300/1180 mm	1250 mm	1000 mm
PF 25T.130	2500 kg/500 mm	244 kg	2	300/1230 mm	1300 mm	1000 mm
PF 25T.150	2500 kg/500 mm	255 kg	2	300/1430 mm	1500 mm	1100 mm
PF 50T.110	5000 kg/500 mm	367 kg	3	340/1040 mm	1100 mm	900 mm
PF 50T.115	5000 kg/500 mm	372 kg	3	340/1090 mm	1150 mm	900 mm
PF 50T.125	5000 kg/500 mm	380 kg	3	340/1190 mm	1250 mm	1000 mm
PF 50T.135	5000 kg/500 mm	403 kg	3	340/1290 mm	1350 mm	1000 mm
PF 50T.155	5000 kg/500 mm	422 kg	3	340/1490 mm	1550 mm	1200 mm
PF 50T.165	5000 kg/500 mm	432 kg	3	340/1590 mm	1650 mm	1200 mm
PF 60T.150	6000 kg/600 mm	663 kg	4	570/1420 mm	1500 mm	1200 mm
PF 60T.170	6000 kg/600 mm	703 kg	4	570/1620 mm	1700 mm	1400 mm
PF 60T.190	6000 kg/600 mm	743 kg	4	570/1820 mm	1900 mm	1600 mm
PF 80T.180	8000 kg/600 mm	781 kg	4	570/1720 mm	1800 mm	1500 mm
PF 80T.200	8000 kg/600 mm	821 kg	4	570/1920 mm	2000 mm	1600 mm
PF 80T.220	8000 kg/600 mm	861 kg	4	570/2120 mm	2200 mm	1800 mm
PF 120T.220	12000 kg/600 mm	1290 kg	4	670/2080 mm	2200 mm	1900 mm

