

# Pozicionér vidlíc s integrovaným bočným posuvom s vidlicami na vodiacej tyči

Označenie	Nosnosť	Hmotnosť	ISO 2328	A	B	C
PJ20T.090	2000 kg/500 mm	225 kg	2A	340-780 mm	900 mm	620 mm
PJ20T.095	2000 kg/500 mm	230 kg	2A	340-830 mm	950 mm	620 mm
PJ20T.100	2000 kg/500 mm	233 kg	2A	340-880 mm	1000 mm	720 mm
PJ20T.105	2000 kg/500 mm	236 kg	2A	340-930 mm	1050 mm	720 mm
PJ20T.110	2000 kg/500 mm	239 kg	2A	340-980 mm	1100 mm	720 mm
PJ20T.115	2000 kg/500 mm	241 kg	2A	340-1030 mm	1150 mm	720 mm
PJ25.T090	2500 kg/500 mm	246 kg	2A	340-780 mm	900 mm	620 mm
PJ25T.095	2500 kg/500 mm	251 kg	2A	340-830 mm	950 mm	620 mm
PJ25T.100	2500 kg/500 mm	254 kg	2A	340-880 mm	1000 mm	720 mm
PJ25T.105	2500 kg/500 mm	256 kg	2A	340-930 mm	1050 mm	720 mm
PJ25T.110	2500 kg/500 mm	260 kg	2A	340-980 mm	1100 mm	720 mm
PJ25T.115	2500 kg/500 mm	264 kg	2A	340-1030 mm	1150 mm	720 mm
PJ25T.125	2500 kg/500 mm	270 kg	2A	340-1130 mm	1250 mm	720 mm
PJ25T.135	2500 kg/500 mm	277 kg	2A	340-1230 mm	1350 mm	830 mm
PJ25T.150	2500 kg/500 mm	288 kg	2A	340-1380 mm	1500 mm	830 mm
PJ35T.110	3500 kg/500 mm	312 kg	3A	340-980 mm	1100 mm	730 mm
PJ35T.115	3500 kg/500 mm	318 kg	3A	340-1030 mm	1150 mm	730 mm
PJ35T.125	3500 kg/500 mm	324 kg	3A	340-1130 mm	1250 mm	730 mm
PJ35T.135	3500 kg/500 mm	334 kg	3A	340-1230 mm	1350 mm	830 mm
PJ35T.150	3500 kg/500 mm	345 kg	3A	340-1380 mm	1500 mm	830 mm
PJ50T.115	5000 kg/500 mm	415 kg	3A	420-1030 mm	1150 mm	800 mm
PJ50T.125	5000 kg/500 mm	428 kg	3A	420-1130 mm	1250 mm	800 mm
PJ50T.135	5000 kg/500 mm	445 kg	3A	420-1230 mm	1350 mm	800 mm
PJ50T.150	5000 kg/500 mm	459 kg	3A	420-1380 mm	1500 mm	850 mm
PJ50T.170	5000 kg/500 mm	468 kg	3A	420-1580 mm	1700 mm	850 mm

