

Pozicionér vidlíc – ťažký rad

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
PFA 25.098	2500 kg/500 mm	124 kg	2	360/870 mm	980 mm	800 mm
PFA 25.104	2500 kg/500 mm	147 kg	2	360/930 mm	1040 mm	800 mm
PFA 25.110	2500 kg/500 mm	150 kg	2	360/990 mm	1100 mm	900 mm
PFA 25.115	2500 kg/500 mm	152 kg	2	360/1040 mm	1150 mm	900 mm
PFA 25.125	2500 kg/500 mm	158 kg	2	360/1140 mm	1250 mm	1000 mm
PFA 25.130	2500 kg/500 mm	160 kg	2	360/1190 mm	1300 mm	1000 mm
PFA 25.150	2500 kg/500 mm	171 kg	2	360/1390 mm	1500 mm	1100 mm
PFA 50.110	5000 kg/500 mm	223 kg	3	400/980 mm	1100 mm	900 mm
PFA 50.115	5000 kg/500 mm	228 kg	3	400/1030 mm	1150 mm	900 mm
PFA 50.125	5000 kg/500 mm	237 kg	3	400/1130 mm	1250 mm	1000 mm
PFA 50.135	5000 kg/500 mm	244 kg	3	400/1230 mm	1350 mm	1000 mm
PFA 50.155	5000 kg/500 mm	254 kg	3	400/1430 mm	1550 mm	1200 mm
PFA 50.165	5000 kg/500 mm	274 kg	3	400/1530 mm	1650 mm	1200 mm
PFA 60.150	6000 kg/600 mm	512 kg	4	515/1365 mm	1500 mm	1200 mm
PFA 60.170	6000 kg/600 mm	552 kg	4	515/1565 mm	1700 mm	1400 mm
PFA 60.190	6000 kg/600 mm	592 kg	4	515/1765 mm	1900 mm	1600 mm
PFA 80.180	8000 kg/600 mm	596 kg	4	515/1665 mm	1800 mm	1500 mm
PFA 80.200	8000 kg/600 mm	636 kg	4	515/1865 mm	2000 mm	1600 mm
PFA 80.220	8000 kg/600 mm	676 kg	4	515/2065 mm	2200 mm	1800 mm
PFA 120.220	12000 kg/600 mm	1050 kg	4	560/2000 mm	2200 mm	1800 mm

