

Pozicionér vidlíc so samostatným bočným posuvom – ťažký rad

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
PFA 25T.098	2500 kg/500 mm	129 kg	2	360/870 mm	980 mm	800 mm
PFA 25T.098	2500 kg/500 mm	152 kg	2	360/930 mm	1040 mm	800 mm
PFA 25T.098	2500 kg/500 mm	155 kg	2	360/990 mm	1100 mm	900 mm
PFA 25T.098	2500 kg/500 mm	157 kg	2	360/1040 mm	1150 mm	900 mm
PFA 25T.098	2500 kg/500 mm	163 kg	2	360/1140 mm	1250 mm	1000 mm
PFA 25T.098	2500 kg/500 mm	167 kg	2	360/1190 mm	1300 mm	1000 mm
PFA 25T.098	2500 kg/500 mm	180 kg	2	360/1390 mm	1500 mm	1100 mm
PFA 50T.110	5000 kg/500 mm	230 kg	3	400/980 mm	1100 mm	900 mm
PFA 50T.115	5000 kg/500 mm	235 kg	3	400/1030 mm	1150 mm	900 mm
PFA 50T.125	5000 kg/500 mm	245 kg	3	400/1130 mm	1250 mm	1000 mm
PFA 50T.135	5000 kg/500 mm	252 kg	3	400/1230 mm	1350 mm	1000 mm
PFA 50T.155	5000 kg/500 mm	272 kg	3	400/1430 mm	1550 mm	1200 mm
PFA 50T.165	5000 kg/500 mm	292 kg	3	400/1530 mm	1650 mm	1200 mm
PFA 60T.150	6000 kg/600 mm	560 kg	4	515/1365 mm	1500 mm	1200 mm
PFA 60T.170	6000 kg/600 mm	600 kg	4	515/1565 mm	1700 mm	1400 mm
PFA 60T.190	6000 kg/600 mm	648 kg	4	515/1765 mm	1900 mm	1600 mm
PFA 80T.180	8000 kg/600 mm	664 kg	4	515/1665 mm	1800 mm	1500 mm
PFA 80T.200	8000 kg/600 mm	704 kg	4	515/1865 mm	2000 mm	1700 mm
PFA 80T.220	8000 kg/600 mm	744 kg	4	515/2065 mm	2200 mm	1900 mm
PFA 120T.220	12000 kg/600 mm	1120 kg	4	560/2000 mm	2200 mm	1900 mm

