

Pozicionér vidlíc so zváranými vidlicami – široké roztvorenie

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
WF 16-A0-12	1600 kg/500 mm	299 kg	2	560/1740 mm	950 mm	750 mm
WF 16-B0-12	1600 kg/500 mm	309 kg	2	560/1840 mm	1050 mm	750 mm
WF 20-A0-12	2000 kg/500 mm	322 kg	2	560/1740 mm	950 mm	750 mm
WF 20-B0-12	2000 kg/500 mm	332 kg	2	560/1840 mm	1050 mm	750 mm
WF 20-C0-12	2000 kg/500 mm	342 kg	2	560/1940 mm	1150 mm	750 mm
WF 23-A0-12	2300 kg/500 mm	325 kg	2	560/1740 mm	950 mm	750 mm
WF 23-B0-12	2300 kg/500 mm	335 kg	2	560/1840 mm	1050 mm	750 mm
WF 23-C0-12	2300 kg/500 mm	345 kg	2	560/1940 mm	1150 mm	750 mm
WF 30-A0-12	3000 kg/500 mm	372 kg	3	560/1840 mm	1050 mm	800 mm
WF 30-B0-12	3000 kg/500 mm	388 kg	3	560/1940 mm	1150 mm	900 mm
WF 30-C0-12	3000 kg/500 mm	401 kg	3	560/2100 mm	1320 mm	900 mm
WF 40-A0-12	4000 kg/500 mm	595 kg	3	560/1940 mm	1150 mm	900 mm
WF 40-B0-12	4000 kg/500 mm	612 kg	3	560/2100 mm	1320 mm	1000 mm
WF 40-C0-12	4000 kg/500 mm	640 kg	3	560/2400 mm	1600 mm	1050 mm
WF 45-A0-12	4500 kg/500 mm	610 kg	3	560/1940 mm	1150 mm	900 mm
WF 45-B0-12	4500 kg/500 mm	627 kg	3	560/2100 mm	1320 mm	1000 mm
WF 45-C0-12	4500 kg/500 mm	655 kg	3	560/2400 mm	1600 mm	1050 mm
WF 55-A0-12	5500 kg/500 mm	657 kg	4	560/2100 mm	1320 mm	1000 mm
WF 55-B0-12	5500 kg/500 mm	685 kg	4	560/2400 mm	1600 mm	1050 mm
WF 65-A0-12	6500 kg/600 mm	815 kg	4	560/2400 mm	1600 mm	1050 mm
WF 65-B0-12	6500 kg/600 mm	840 kg	4	560/2600 mm	1800 mm	1200 mm
WF 80-A0-12	8000 kg/600 mm	1590 kg	4	660/2390 mm	1800 mm	1250 mm
WF 90-A0-12	9000 kg/600 mm	1680 kg	4	660/2590 mm	2000 mm	1350 mm

