

Pozicionér vidlíc – široké roztvorenie

Označenie	Nosnosť	Hmotnosť	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
WA 16-A0	1600 kg/500 mm	242 kg	2	560/1740 mm	950 mm	750 mm
WA 16-B0	1600 kg/500 mm	252 kg	2	560/1840 mm	1050 mm	750 mm
WA 20-A0	2000 kg/500 mm	266 kg	2	560/1740 mm	950 mm	750 mm
WA 20-B0	2000 kg/500 mm	276 kg	2	560/1840 mm	1050 mm	750 mm
WA 20-C0	2000 kg/500 mm	286 kg	2	560/1940 mm	1150 mm	750 mm
WA 23-A0	2300 kg/500 mm	248 kg	2	560/1740 mm	950 mm	750 mm
WA 23-B0	2300 kg/500 mm	258 kg	2	560/1840 mm	1050 mm	750 mm
WA 23-C0	2300 kg/500 mm	268 kg	2	560/1940 mm	1150 mm	750 mm
WA 30-A0	3000 kg/500 mm	282 kg	3	560/1840 mm	1050 mm	800 mm
WA 30-B0	3000 kg/500 mm	300 kg	3	560/1940 mm	1150 mm	900 mm
WA 30-C0	3000 kg/500 mm	323 kg	3	560/2100 mm	1320 mm	900 mm
WA 40-A0	4000 kg/500 mm	442 kg	3	560/1940 mm	1150 mm	900 mm
WA 40-B0	4000 kg/500 mm	459 kg	3	560/2100 mm	1320 mm	1000 mm
WA 40-C0	4000 kg/500 mm	487 kg	3	560/2400 mm	1600 mm	1050 mm
WA 45-A0	4500 kg/500 mm	456 kg	3	560/1940 mm	1150 mm	900 mm
WA 45-B0	4500 kg/500 mm	473 kg	3	560/2100 mm	1320 mm	1000 mm
WA 45-C0	4500 kg/500 mm	501 kg	3	560/2400 mm	1600 mm	1050 mm
WA 55-A0	5500 kg/500 mm	530 kg	4	560/2100 mm	1320 mm	1000 mm
WA 55-B0	5500 kg/500 mm	558 kg	4	560/2400 mm	1600 mm	1050 mm
WA 65-A0	6500 kg/600 mm	805 kg	4	560/2400 mm	1600 mm	1050 mm
WA 65-B0	6500 kg/600 mm	830 kg	4	560/2600 mm	1800 mm	1200 mm
WA 80-A0	8000 kg/600 mm	1510 kg	4	660/2390 mm	1800 mm	1250 mm
WA 90-A0	9000 kg/600 mm	1595 kg	4	600/2590 mm	2000 mm	1350 mm

