

Otočné zariadenie 360° s pozicionérom vidlíc – široké roztvorenie

Označenie	Nosnosť	Hmotnosť	Kapacita rotácie	ISO	Roztvorenie vidlíc	Šírka zariadenia	Min. šírka nosiča vidlíc
WF 16R	1600 kg/500 mm	535 kg	1200 kg/500 mm	2	480/1540 mm	950 mm	750 mm
WF 23R	2300 kg/500 mm	562 kg	1600 kg/500 mm	2	480/1540 mm	950 mm	750 mm
WF 30R	3000 kg/500 mm	680 kg	2500 kg/500 mm	3	450/1640 mm	1150 mm	900 mm
WF 40R	4000 kg/500 mm	860 kg	2800 kg/500 mm	3	450/1640 mm	1150 mm	1050 mm
WF 45R	4500 kg/500 mm	940 kg	4000 kg/500 mm	3	560/1820 mm	1150 mm	1050 mm
WF 55R	4500 kg/600 mm	990 kg	4000 kg/500 mm	4	560/1820 mm	1150 mm	1230 mm
WF 60R	5000 kg/600 mm	1050 kg	4500 kg/600 mm	4	560/1900 mm	1250 mm	1230 mm
WF 70R	7000 kg/600 mm	1700 kg	6000 kg/600 mm	4	560/1950 mm	1320 mm	1200 mm

