

Zvierajúce otočné vidlice 360°

Označenie	Hmotnosť	ISO 2328	Nosnosť vidlíc	Nosnosť zariadenia	A	B	C
HFR 10-B0-12	520 kg	2	1600 kg/500 mm	1000 kg/500 mm	360/1500 mm	950 mm	750 mm
HFR 10-C0-12	530 kg	2	1600 kg/500 mm	1000 kg/500 mm	360/1600 mm	1050 mm	750 mm
HFR 14-B0-12	530 kg	2	2000 kg/500 mm	1400 kg/500 mm	450/1690 mm	950 mm	750 mm
HFR 14-C0-12	540 kg	2	2000 kg/500 mm	1400 kg/500 mm	360/1600 mm	1050 mm	750 mm
HFR 14-D0-12	550 kg	2	2000 kg/500 mm	1400 kg/500 mm	550/1980 mm	1150 mm	750 mm
HFR 18-A0-12	526 kg	2	1800 kg/500 mm	1800 kg/500 mm	480/1700 mm	950 mm	750 mm
HFR 18-B0-12	536 kg	2	2300 kg/500 mm	1800 kg/500 mm	360/1580 mm	1050 mm	750 mm
HFR 18-B1-12	536 kg	2	2300 kg/500 mm	1800 kg/500 mm	480/1800 mm	1050 mm	750 mm
HFR 18-C0-12	546 kg	2	2300 kg/500 mm	1800 kg/500 mm	480/1920 mm	1150 mm	750 mm
HFR 18-D0-12	556 kg	2	2300 kg/500 mm	1800 kg/500 mm	360/1780 mm	1250 mm	750 mm
HFR 22-A0-12	577 kg	2/3	2500 kg/500 mm	2200 kg/500 mm	430/1660 mm	950 mm	750 mm
HFR 22-B1-12	587 kg	2/3	2500 kg/500 mm	2200 kg/500 mm	320/1540 mm	1050 mm	750 mm
HFR 22-C0-12	597 kg	2/3	2500 kg/500 mm	2200 kg/500 mm	450/1900 mm	1150 mm	750 mm
HFR 22-D1-12	607 kg	2/3	2500 kg/500 mm	2200 kg/500 mm	320/1740 mm	1250 mm	750 mm
HFR 26-A0-12	679 kg	3	3200 kg/500 mm	2600 kg/500 mm	450/1800 mm	1050 mm	900 mm
HFR 26-B1-12	687 kg	3	3200 kg/500 mm	2600 kg/500 mm	320/1640 mm	1150 mm	900 mm
HFR 26-C0-12	695 kg	3	3200 kg/500 mm	2600 kg/500 mm	450/2000 mm	1250 mm	900 mm
HFR 26-D1-12	703 kg	3	3200 kg/500 mm	2600 kg/500 mm	320/1810 mm	1320 mm	900 mm
HFR 30-A0-12	704 kg	3	3600 kg/500 mm	2800 kg/500 mm	320/1620 mm	1150 mm	900 mm
HFR 30-B0-12	715 kg	3	3600 kg/500 mm	2800 kg/500 mm	450/1970 mm	1250 mm	900 mm
HFR 30-C0-12	725 kg	3	3600 kg/500 mm	2800 kg/500 mm	320/1780 mm	1320 mm	900 mm
HFR 35-A0-12	880 kg	3	4200 kg/500 mm	3500 kg/500 mm	320/1620 mm	1150 mm	1050 mm
HFR 35-B0-12	905 kg	3	4200 kg/500 mm	3500 kg/500 mm	320/1780 mm	1320 mm	1050 mm
HFR 35-C0-12	923 kg	3	4200 kg/500 mm	3500 kg/500 mm	450/2180 mm	1450 mm	1050 mm
HFR 40-A0-12	950 kg	3	4800 kg/500 mm	4000 kg/500 mm	260/1560 mm	1150 mm	1050 mm
HFR 40-B0-12	985 kg	3	4800 kg/500 mm	4000 kg/500 mm	450/2050 mm	1320 mm	1050 mm
HFR 40-C0-12	1025 kg	3	4800 kg/500 mm	4000 kg/500 mm	450/2180 mm	1450 mm	1050 mm
HFR 45-A0-12	1220 kg	4	5000 kg/600 mm	3800 kg/600 mm	350/1970 mm	1450 mm	1230 mm
HFR 45-B0-12	1280 kg	4	5000 kg/600 mm	3800 kg/600 mm	450/2320 mm	1600 mm	1230 mm

