

Zvierajúce čelúste balíkov

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	C
HB 10-A0T-09	369 kg	1000 kg/500 mm	2	450/1590 mm	950 mm	750 mm
HB 10-A0T-10	389 kg	1000 kg/500 mm	2	450/1590 mm	950 mm	750 mm
HB 10-A1T-09	375 kg	1000 kg/500 mm	2	550/1790 mm	950 mm	750 mm
HB 10-A1T-10	394 kg	1000 kg/500 mm	2	550/1790 mm	950 mm	750 mm
HB 14-A0T-09	382 kg	1400 kg/500 mm	2	550/1790 mm	950 mm	750 mm
HB 14-A0T-10	402 kg	1400 kg/500 mm	2	550/1790 mm	950 mm	750 mm
HB 14-B0T-09	387 kg	1400 kg/500 mm	2	450/1690 mm	1050 mm	750 mm
HB 14-B0T-10	412 kg	1400 kg/500 mm	2	450/1690 mm	1050 mm	750 mm
HB 14-C0T-09	402 kg	1400 kg/500 mm	2	450/1790 mm	1150 mm	750 mm
HB 14-C0T-10	392 kg	1400 kg/500 mm	2	450/1790 mm	1150 mm	750 mm
HB 14-C1T-09	412 kg	1400 kg/500 mm	2	650/2190 mm	1150 mm	750 mm
HB 14-C1T-10	432 kg	1400 kg/500 mm	2	650/2190 mm	1150 mm	750 mm
HB 18-A0T-10	448 kg	1800 kg/500 mm	2	560/1780 mm	950 mm	750 mm
HB 18-A0T-12	460 kg	1800 kg/500 mm	2	560/1780 mm	950 mm	750 mm
HB 18-B0T-10	446 kg	1800 kg/500 mm	2	460/1680 mm	1050 mm	750 mm
HB 18-B0T-12	461 kg	1800 kg/500 mm	2	460/1680 mm	1050 mm	750 mm
HB 18-C0T-10	453 kg	1800 kg/500 mm	2	560/1980 mm	1150 mm	750 mm
HB 18-C0T-12	485 kg	1800 kg/500 mm	2	560/1980 mm	1150 mm	750 mm
HB 18-D0T-10	468 kg	1800 kg/500 mm	2	460/1880 mm	1250 mm	850 mm
HB 18-D0T-12	494 kg	1800 kg/500 mm	2	460/1880 mm	1250 mm	850 mm
HB 22-A0T-10	492 kg	2200 kg/500 mm	2	570/1800 mm	950 mm	750 mm
HB 22-A0T-12	460 kg	2200 kg/500 mm	2	570/1800 mm	950 mm	750 mm
HB 22-B0T-10	457 kg	2200 kg/500 mm	2	660/2080 mm	1050 mm	750 mm
HB 22-B0T-12	485 kg	2200 kg/500 mm	2	660/2080 mm	1050 mm	750 mm
HB 22-C0T-10	469 kg	2200 kg/500 mm	2	560/1980 mm	1150 mm	750 mm
HB 22-C0T-12	494 kg	2200 kg/500 mm	2	560/1980 mm	1150 mm	750 mm
HB 22-D0T-10	480 kg	2200 kg/500 mm	2	570/2100 mm	1250 mm	850 mm
HB 22-D0T-12	508 kg	2200 kg/500 mm	2	570/2100 mm	1250 mm	850 mm
HB 26-A0T-10	470 kg	2600 kg/500 mm	2/3	550/1860 mm	1050 mm	750 mm
HB 26-A0T-12	492 kg	2600 kg/500 mm	2/3	550/1860 mm	1050 mm	750 mm
HB 26-B0T-10	484 kg	2600 kg/500 mm	2/3	670/2200 mm	1150 mm	750 mm
HB 26-B0T-12	509 kg	2600 kg/500 mm	2/3	670/2200 mm	1150 mm	750 mm
HB 26-C0T-10	497 kg	2600 kg/500 mm	2/3	530/2020 mm	1250 mm	850 mm
HB 26-C0T-12	522 kg	2600 kg/500 mm	2/3	530/2020 mm	1250 mm	850 mm
HB 26-D0T-10	505 kg	2600 kg/500 mm	2/3	670/2320 mm	1320 mm	850 mm
HB 26-D0T-12	530 kg	2600 kg/500 mm	2/3	670/2320 mm	1320 mm	850 mm

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	C
HB 30-A0T-12	824 kg	3000 kg/500 mm	3	630/2090 mm	1150 mm	850 mm
HB 30-A0T-14	849 kg	3000 kg/500 mm	3	630/2090 mm	1150 mm	850 mm
HB 30-B0T-12	837 kg	3000 kg/500 mm	3	520/1990 mm	1250 mm	850 mm
HB 30-B0T-14	867 kg	3000 kg/500 mm	3	520/1990 mm	1250 mm	850 mm
HB 30-C0T-12	852 kg	3000 kg/500 mm	3	640/2300 mm	1320 mm	850 mm
HB 30-C0T-14	883 kg	3000 kg/500 mm	3	640/2300 mm	1320 mm	850 mm
HB 35-A0T-12	819 kg	3500 kg/500 mm	3	430/1730 mm	1150 mm	900 mm
HB 35-A0T-14	844 kg	3500 kg/500 mm	3	430/1730 mm	1150 mm	900 mm
HB 35-B0T-12	829 kg	3500 kg/500 mm	3	690/2420 mm	1320 mm	1000 mm
HB 35-B0T-14	861 kg	3500 kg/500 mm	3	690/2420 mm	1320 mm	1000 mm
HB 35-C0T-12	846 kg	3500 kg/500 mm	3	560/2290 mm	1450 mm	1000 mm
HB 35-C0T-14	874 kg	3500 kg/500 mm	3	560/2290 mm	1450 mm	1000 mm
HB 42-A0T-12	931 kg	4200 kg/500 mm	3	600/2070 mm	1150 mm	900 mm
HB 42-A0T-14	965 kg	4200 kg/500 mm	3	600/2070 mm	1150 mm	900 mm
HB 42-A0T-16	992 kg	4200 kg/500 mm	3	600/2070 mm	1150 mm	900 mm
HB 42-B0T-12	959 kg	4200 kg/500 mm	3	560/2160 mm	1320 mm	1000 mm
HB 42-B0T-14	987 kg	4200 kg/500 mm	3	560/2160 mm	1320 mm	1000 mm
HB 42-B0T-16	1016 kg	4200 kg/500 mm	3	560/2160 mm	1320 mm	1000 mm
HB 42-C0T-12	990 kg	4200 kg/500 mm	3	680/2500 mm	1450 mm	1050 mm
HB 42-C0T-14	1023 kg	4200 kg/500 mm	3	680/2500 mm	1450 mm	1050 mm
HB 42-C0T-16	1059 kg	4200 kg/500 mm	3	680/2500 mm	1450 mm	1050 mm
HB 45-A0T-12	1030 kg	4500 kg/600 mm	4	600/2320 mm	1450 mm	1050 mm
HB 45-A0T-14	1069 kg	4500 kg/600 mm	4	600/2320 mm	1450 mm	1050 mm
HB 45-A0T-16	1100 kg	4500 kg/600 mm	4	600/2320 mm	1450 mm	1050 mm
HB 45-B0T-12	1052 kg	4500 kg/600 mm	4	700/2670 mm	1600 mm	1050 mm
HB 45-B0T-14	1088 kg	4500 kg/600 mm	4	700/2670 mm	1600 mm	1050 mm
HB 45-B0T-16	1129 kg	4500 kg/600 mm	4	700/2670 mm	1600 mm	1050 mm
HB 60-A0T-14	1295 kg	6000 kg/600 mm	4	630/2510 mm	1600 mm	1050 mm
HB 60-A0T-16	1360 kg	6000 kg/600 mm	4	630/2510 mm	1600 mm	1050 mm
HB 60-B0T-14	1330 kg	6000 kg/600 mm	4	710/2870 mm	1800 mm	1050 mm
HB 60-B0T-16	1395 kg	6000 kg/600 mm	4	710/2870 mm	1800 mm	1050 mm
HB 80-A0T-16	2800 kg	8000 kg/800 mm	4	650/3300 mm	2500 mm	

