

# Zvierajúce čeluste balíkov s pogumovanými čelustami

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	Min. šírka nosiča vidlíc
HBG 10-A0T-09	400 kg	1000 kg/500 mm	2	410/1550 mm	950 mm	750 mm
HBG 10-A0T-10	420 kg	1000 kg/500 mm	2	410/1550 mm	950 mm	750 mm
HBG 10-A1T-09	405 kg	1000 kg/500 mm	2	510/1720 mm	950 mm	750 mm
HBG 10-A1T-10	425 kg	1000 kg/500 mm	2	510/1720 mm	950 mm	750 mm
HBG 14-A0T-09	407 kg	1400 kg/500 mm	2	510/1750 mm	950 mm	750 mm
HBG 14-A0T-10	427 kg	1400 kg/500 mm	2	510/1750 mm	950 mm	750 mm
HBG 14-B0T-09	420 kg	1400 kg/500 mm	2	410/1650 mm	1050 mm	750 mm
HBG 14-B0T-10	440 kg	1400 kg/500 mm	2	410/1650 mm	1050 mm	750 mm
HBG 14-C0T-09	419 kg	1400 kg/500 mm	2	530/1850 mm	1150 mm	750 mm
HBG 14-C0T-10	439 kg	1400 kg/500 mm	2	520/1840 mm	1150 mm	750 mm
HBG 14-C1T-09	416 kg	1400 kg/500 mm	2	320/1450 mm	1150 mm	750 mm
HBG 14-C1T-10	436 kg	1400 kg/500 mm	2	320/1440 mm	1150 mm	750 mm
HBG 18-A0T-10	437 kg	1800 kg/500 mm	2	520/1740 mm	950 mm	750 mm
HBG 18-A0T-12	469 kg	1800 kg/500 mm	2	520/1740 mm	950 mm	750 mm
HBG 18-B0T-10	448 kg	1800 kg/500 mm	2	410/1640 mm	1050 mm	750 mm
HBG 18-B0T-12	483 kg	1800 kg/500 mm	2	410/1640 mm	1050 mm	750 mm
HBG 18-C0T-10	457 kg	1800 kg/500 mm	2	540/1940 mm	1150 mm	750 mm
HBG 18-C0T-12	492 kg	1800 kg/500 mm	2	540/1940 mm	1150 mm	750 mm
HBG 18-D0T-10	467 kg	1800 kg/500 mm	2	420/1440 mm	1250 mm	850 mm
HBG 18-D0T-12	503 kg	1800 kg/500 mm	2	420/1440 mm	1250 mm	850 mm
HBG 22-A0T-10	441 kg	2200 kg/500 mm	2	530/1760 mm	950 mm	750 mm
HBG 22-A0T-12	477 kg	2200 kg/500 mm	2	530/1760 mm	950 mm	750 mm
HBG 22-B0T-10	452 kg	2200 kg/500 mm	2	620/2040 mm	1050 mm	750 mm
HBG 22-B0T-12	487 kg	2200 kg/500 mm	2	620/2040 mm	1050 mm	750 mm
HBG 22-C0T-10	462 kg	2200 kg/500 mm	2	520/1940 mm	1150 mm	750 mm
HBG 22-C0T-12	497 kg	2200 kg/500 mm	2	520/1940 mm	1150 mm	750 mm
HBG 22-D0T-10	471 kg	2200 kg/500 mm	2	530/2060 mm	1250 mm	850 mm
HBG 22-D0T-12	507 kg	2200 kg/500 mm	2	530/2060 mm	1250 mm	850 mm
HBG 26-A0T-10	458 kg	2600 kg/500 mm	2/3	510/1820 mm	1050 mm	750 mm
HBG 26-A0T-12	490 kg	2600 kg/500 mm	2/3	510/1820 mm	1050 mm	750 mm
HBG 26-B0T-10	467 kg	2600 kg/500 mm	2/3	630/2140 mm	1150 mm	750 mm
HBG 26-B0T-12	499 kg	2600 kg/500 mm	2/3	630/2140 mm	1150 mm	750 mm

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	Min. šírka nosiča vidlíc
HBG 26-C0T-10	708 kg	2600 kg/500 mm	2/3	490/1880 mm	1250 mm	850 mm
HBG 26-C0T-12	738 kg	2600 kg/500 mm	2/3	490/1880 mm	1250 mm	850 mm
HBG 26-D0T-10	728 kg	2600 kg/500 mm	2/3	630/2280 mm	1320 mm	850 mm
HBG 26-D0T-12	758 kg	2600 kg/500 mm	2/3	630/2280 mm	1320 mm	850 mm
HBG 30-A0T-12	758 kg	3000 kg/500 mm	3	570/2030 mm	1150 mm	850 mm
HBG 30-A0T-14	778 kg	3000 kg/500 mm	3	570/2030 mm	1150 mm	850 mm
HBG 30-B0T-12	769 kg	3000 kg/500 mm	3	470/1930 mm	1250 mm	850 mm
HBG 30-B0T-14	789 kg	3000 kg/500 mm	3	470/1930 mm	1250 mm	850 mm
HBG 30-C0T-12	803 kg	3000 kg/500 mm	3	600/1900 mm	1320 mm	850 mm
HBG 30-C0T-14	823 kg	3000 kg/500 mm	3	600/1900 mm	1320 mm	850 mm

