

Zvierajúce otočné čeľuste balíkov 360°

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	Min. šírka nosiča vidlíc
HBR 10-A0-09	545 kg	1000 kg/500 mm	2	450/1590 mm	950 mm	750 mm
HBR 10-A0-10	565 kg	1000 kg/500 mm	2	450/1590 mm	950 mm	750 mm
HBR 10-A1-09	550 kg	1000 kg/500 mm	2	550/1790 mm	950 mm	750 mm
HBR 10-A1-10	570 kg	1000 kg/500 mm	2	550/1790 mm	950 mm	750 mm
HBR 14-A0-09	551 kg	1400 kg/500 mm	2	550/1790 mm	950 mm	750 mm
HBR 14-A0-10	572 kg	1400 kg/500 mm	2	550/1790 mm	950 mm	750 mm
HBR 14-B0-09	559 kg	1400 kg/500 mm	2	450/1690 mm	1050 mm	750 mm
HBR 14-B0-10	580 kg	1400 kg/500 mm	2	450/1690 mm	1050 mm	750 mm
HBR 14-C0-09	562 kg	1400 kg/500 mm	2	450/1790 mm	1150 mm	750 mm
HBR 14-C0-10	586 kg	1400 kg/500 mm	2	450/1790 mm	1150 mm	750 mm
HBR 14-C1-09	558 kg	1400 kg/500 mm	2	650/2190 mm	1150 mm	750 mm
HBR 14-C1-10	584 kg	1400 kg/500 mm	2	650/2190 mm	1150 mm	750 mm
HBR 18-A0-10	647 kg	1800 kg/500 mm	2	560/1780 mm	950 mm	750 mm
HBR 18-A0-12	660 kg	1800 kg/500 mm	2	560/1780 mm	950 mm	750 mm
HBR 18-B0-10	661 kg	1800 kg/500 mm	2	450/1680 mm	1050 mm	750 mm
HBR 18-B0-12	670 kg	1800 kg/500 mm	2	450/1680 mm	1050 mm	750 mm
HBR 18-C0-10	679 kg	1800 kg/500 mm	2	560/1980 mm	1150 mm	750 mm
HBR 18-C0-12	689 kg	1800 kg/500 mm	2	560/1980 mm	1150 mm	750 mm
HBR 18-D0-10	699 kg	1800 kg/500 mm	2	460/1880 mm	1250 mm	750 mm
HBR 18-D0-12	713 kg	1800 kg/500 mm	2	460/1880 mm	1250 mm	750 mm
HBR 22-A0-10	586 kg	2200 kg/500 mm	2	570/1800 mm	950 mm	750 mm
HBR 22-A0-12	597 kg	2200 kg/500 mm	2	570/1800 mm	950 mm	750 mm
HBR 22-B0-10	608 kg	2200 kg/500 mm	2	660/2080 mm	1050 mm	750 mm
HBR 22-B0-12	618 kg	2200 kg/500 mm	2	660/2080 mm	1050 mm	750 mm
HBR 22-C0-10	614 kg	2200 kg/500 mm	2	560/1980 mm	1150 mm	750 mm
HBR 22-C0-12	625 kg	2200 kg/500 mm	2	560/1980 mm	1150 mm	750 mm
HBR 22-D0-10	635 kg	2200 kg/500 mm	2	570/2100 mm	1250 mm	750 mm
HBR 22-D0-12	652 kg	2200 kg/500 mm	2	570/2100 mm	1250 mm	750 mm
HBR 26-A0-10	655 kg	2600 kg/500 mm	2/3	550/1860 mm	1050 mm	900 mm
HBR 26-A0-12	687 kg	2600 kg/500 mm	2/3	550/1860 mm	1050 mm	900 mm
HBR 26-B0-10	664 kg	2600 kg/500 mm	2/3	670/2200 mm	1150 mm	900 mm
HBR 26-B0-12	696 kg	2600 kg/500 mm	2/3	670/2200 mm	1150 mm	900 mm
HBR 26-C0-10	674 kg	2600 kg/500 mm	2/3	530/2020 mm	1250 mm	900 mm

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	Min. šírka nosiča vidlíc
HBR 26-C0-12	705 kg	2600 kg/500 mm	2/3	530/2020 mm	1250 mm	900 mm
HBR 26-D0-10	683 kg	2600 kg/500 mm	2/3	670/2320 mm	1320 mm	900 mm
HBR 26-D0-12	712 kg	2600 kg/500 mm	2/3	670/2320 mm	1320 mm	900 mm
HBR 30-A0-12	955 kg	3000 kg/500 mm	3	620/2090 mm	1150 mm	900 mm
HBR 30-A0-14	974 kg	3000 kg/500 mm	3	620/2090 mm	1150 mm	900 mm
HBR 30-B0-12	966 kg	3000 kg/500 mm	3	520/1990 mm	1250 mm	900 mm
HBR 30-B0-14	985 kg	3000 kg/500 mm	3	520/1990 mm	1250 mm	900 mm
HBR 30-C0-12	999 kg	3000 kg/500 mm	3	640/2300 mm	1320 mm	900 mm
HBR 30-C0-14	1019 kg	3000 kg/500 mm	3	640/2300 mm	1320 mm	900 mm
HBR 35-A0-12	1028 kg	3500 kg/500 mm	3	430/1730 mm	1150 mm	1050 mm
HBR 35-A0-14	1048 kg	3500 kg/500 mm	3	430/1730 mm	1150 mm	1050 mm
HBR 35-B0-12	1073 kg	3500 kg/500 mm	3	690/2420 mm	1320 mm	1050 mm
HBR 35-B0-14	1094 kg	3500 kg/500 mm	3	690/2420 mm	1320 mm	1050 mm
HBR 35-C0-12	1092 kg	3500 kg/500 mm	3	560/2290 mm	1450 mm	1050 mm
HBR 35-C0-14	1121 kg	3500 kg/500 mm	3	560/2290 mm	1450 mm	1050 mm
HBR 42-A0-12	1135 kg	4200 kg/500 mm	3	600/2070 mm	1150 mm	1050 mm
HBR 42-A0-14	1165 kg	4200 kg/500 mm	3	600/2070 mm	1150 mm	1050 mm
HBR 42-A0-16	1203 kg	4200 kg/500 mm	3	600/2070 mm	1150 mm	1050 mm
HBR 42-B0-12	1160 kg	4200 kg/500 mm	3	560/2160 mm	1320 mm	1050 mm
HBR 42-B0-14	1190 kg	4200 kg/500 mm	3	560/2160 mm	1320 mm	1050 mm
HBR 42-B0-16	1230 kg	4200 kg/500 mm	3	560/2160 mm	1320 mm	1050 mm
HBR 42-C0-12	1277 kg	4200 kg/500 mm	3	680/2500 mm	1450 mm	1050 mm
HBR 42-C0-14	1218 kg	4200 kg/500 mm	3	680/2500 mm	1450 mm	1050 mm
HBR 42-C0-16	1255 kg	4200 kg/500 mm	3	680/2500 mm	1450 mm	1050 mm

