

Zvierajúce zariadenie s bočným posuvom a mechanicky otočnými vidlicami 90°

Označenie	Hmotnosť	Nosnosť vidlíc	Nosnosť zariadenia	ISO 2328	B	C	Palety
HP 10-A0T-10	372 kg	1400 kg/500 mm	1000 kg/500 mm	2	950 mm	750 mm	EURO
HP 10-A0T-12	385 kg	1400 kg/500 mm	1000 kg/500 mm	2	950 mm	750 mm	EURO
HP 14-A0T-10	390 kg	1800 kg/500 mm	1400 kg/500 mm	2	1050 mm	750 mm	EURO
HP 14-A0T-12	407 kg	1800 kg/500 mm	1400 kg/500 mm	2	1050 mm	750 mm	EURO
HP 18-A0T-12	433 kg	2300 kg/500 mm	1800 kg/500 mm	2	1050 mm	750 mm	EURO
HP 18-B0T-12	454 kg	2300 kg/500 mm	1800 kg/500 mm	2	1150 mm	750 mm	EURO
HP 22-A0T-12	431 kg	2600 kg/500 mm	2200 kg/500 mm	2	1050 mm	750 mm	EURO
HP 22-B0T-12	452 kg	2600 kg/500 mm	2200 kg/500 mm	2	1150 mm	750 mm	EURO
HP 26-A0T-12	470 kg	3200 kg/500 mm	2600 kg/500 mm	3	1050 mm	750 mm	EURO
HP 26-B0T-12	483 kg	3200 kg/500 mm	2600 kg/500 mm	3	1150 mm	750 mm	EURO
HP 30-A0T-12	742 kg	3500 kg/500 mm	3000 kg/500 mm	3	1150 mm	800 mm	EURO
HP 30-B0T-12	758 kg	3500 kg/500 mm	3000 kg/500 mm	3	1250 mm	850 mm	EURO

