

# Zvierajúci mechanizmus - bez vidlíc

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	Min. šírka nosiča vidlíc
H 10-A0	195 kg	1000 kg/500 mm	2	450/1610 mm	870 mm	750 mm
H 10-B0	205 kg	1000 kg/500 mm	2	360/1500 mm	950 mm	750 mm
H 10-C0	215 kg	1000 kg/500 mm	2	360/1580 mm	1050 mm	750 mm
H 14-A0	210 kg	1400 kg/500 mm	2	450/1610 mm	870 mm	750 mm
H 14-B0	215 kg	1400 kg/500 mm	2	450/1690 mm	950 mm	750 mm
H 14-C0	220 kg	1400 kg/500 mm	2	360/1600 mm	1050 mm	750 mm
H 14-D0	225 kg	1400 kg/500 mm	2	550/1980 mm	1150 mm	750 mm
H 18-A0	215 kg	1800 kg/500 mm	2	480/1700 mm	950 mm	750 mm
H 18-B0	220 kg	1800 kg/500 mm	2	480/1800 mm	1050 mm	750 mm
H 18-B1	215 kg	1800 kg/500 mm	2	360/1580 mm	1050 mm	750 mm
H 18-C0	224 kg	1800 kg/500 mm	2	480/1900 mm	1150 mm	750 mm
H 18-D0	228 kg	1800 kg/500 mm	2	360/1780 mm	1250 mm	850 mm
H 22-A0	215 kg	2200 kg/500 mm	2	450/1700 mm	950 mm	750 mm
H 22-B0	220 kg	2200 kg/500 mm	2	320/1540 mm	1050 mm	750 mm
H 22-C0	225 kg	2200 kg/500 mm	2	450/1900 mm	1150 mm	750 mm
H 22-D0	230 kg	2200 kg/500 mm	2	320/1740 mm	1250 mm	750 mm
H 26-A0	225 kg	2600 kg/500 mm	2/3	450/1800 mm	1050 mm	850 mm
H 26-B0	230 kg	2600 kg/500 mm	2/3	320/1640 mm	1150 mm	850 mm
H 26-C0	235 kg	2600 kg/500 mm	2/3	450/2000 mm	1250 mm	850 mm
H 26-D0	242 kg	2600 kg/500 mm	2/3	320/1810 mm	1320 mm	850 mm
H 30-A0	525 kg	3000 kg/500 mm	3	320/1620 mm	1150 mm	850 mm
H 30-B0	545 kg	3000 kg/500 mm	3	450/1970 mm	1250 mm	850 mm
H 30-C0	550 kg	3000 kg/500 mm	3	320/1780 mm	1320 mm	850 mm
H 35-A0	530 kg	3500 kg/500 mm	3	320/1620 mm	1150 mm	900 mm
H 35-B0	565 kg	3500 kg/500 mm	3	320/1790 mm	1320 mm	1000 mm
H 35-C0	580 kg	3500 kg/500 mm	3	450/2180 mm	1450 mm	1000 mm
H 40-A0	540 kg	4000 kg/500 mm	3	320/1620 mm	1150 mm	900 mm
H 40-B0	570 kg	4000 kg/500 mm	3	450/2050 mm	1320 mm	1000 mm
H 40-C0	595 kg	4000 kg/500 mm	3	450/2180 mm	1450 mm	1000 mm
H 45-A0	621 kg	3800 kg/600 mm	4	350/1970 mm	1450 mm	1050 mm

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	Min. šírka nosiča vidlíc
H 45-B0	661 kg	3800 kg/600 mm	4	450/2320 mm	1600 mm	1050 mm
H 60-A0	960 kg	5000 kg/600 mm	4	380/2200 mm	1600 mm	1050 mm
H 60-B0	1020 kg	5000 kg/600 mm	4	380/2400 mm	1800 mm	1050 mm

