

Zvierajúci mechanizmus otočný 360° - bez vidlíc

Označenie	Hmotnosť	Nosnosť	ISO 2328	A	B	Min. šírka nosiča vidlíc
HR 10-A0	345 kg	1000 kg/500 mm	2	450/1610 mm	870 mm	750 mm
HR 10-B0	355 kg	1000 kg/500 mm	2	360/1500 mm	950 mm	750 mm
HR 10-C0	365 kg	1000 kg/500 mm	2	360/1580 mm	1050 mm	750 mm
HR 14-A0	360 kg	1400 kg/500 mm	2	450/1610 mm	870 mm	750 mm
HR 14-B0	365 kg	1400 kg/500 mm	2	450/1690 mm	950 mm	750 mm
HR 14-C0	370 kg	1400 kg/500 mm	2	360/1600 mm	1050 mm	750 mm
HR 14-D0	375 kg	1400 kg/500 mm	2	550/1980 mm	1150 mm	750 mm
HR 18-A0	365 kg	1800 kg/500 mm	2	480/1700 mm	950 mm	750 mm
HR 18-B0	370 kg	1800 kg/500 mm	2	480/1800 mm	1050 mm	750 mm
HR 18-B1	368 kg	1800 kg/500 mm	2	360/1580 mm	1050 mm	750 mm
HR 18-C0	380 kg	1800 kg/500 mm	2	480/1900 mm	1150 mm	750 mm
HR 18-D0	389 kg	1800 kg/500 mm	2	360/1780 mm	1250 mm	850 mm
HR 22-A0	369 kg	2200 kg/500 mm	2	450/1700 mm	950 mm	750 mm
HR 22-B0	375 kg	2200 kg/500 mm	2	320/1540 mm	1050 mm	750 mm
HR 22-C0	382 kg	2200 kg/500 mm	2	450/1900 mm	1150 mm	750 mm
HR 22-D0	388 kg	2200 kg/500 mm	2	320/1740 mm	1250 mm	750 mm
HR 26-A0	440 kg	2600 kg/500 mm	2/3	450/1800 mm	1050 mm	900 mm
HR 26-B0	447 kg	2600 kg/500 mm	2/3	320/1640 mm	1150 mm	900 mm
HR 26-C0	456 kg	2600 kg/500 mm	2/3	450/2000 mm	1250 mm	900 mm
HR 26-D0	468 kg	2600 kg/500 mm	2/3	320/1810 mm	1320 mm	900 mm
HR 30-A0	725 kg	3000 kg/500 mm	3	320/1620 mm	1150 mm	900 mm
HR 30-B0	740 kg	3000 kg/500 mm	3	450/1970 mm	1250 mm	900 mm
HR 30-C0	752 kg	3000 kg/500 mm	3	320/1780 mm	1320 mm	900 mm
HR 35-A0	795 kg	3500 kg/500 mm	3	320/1620 mm	1150 mm	1050 mm
HR 35-B0	810 kg	3500 kg/500 mm	3	320/1790 mm	1320 mm	1050 mm
HR 35-C0	827 kg	3500 kg/500 mm	3	450/2180 mm	1450 mm	1050 mm
HR 40-A0	812 kg	4000 kg/500 mm	3	320/1620 mm	1150 mm	1050 mm
HR 40-B0	821 kg	4000 kg/500 mm	3	450/2050 mm	1320 mm	1050 mm
HR 40-C0	831 kg	4000 kg/500 mm	3	450/2180 mm	1450 mm	1050 mm
HR 45-A0	1080 kg	3800 kg/600 mm	4	350/1970 mm	1450 mm	1230 mm
HR 45-B0	1125 kg	3800 kg/600 mm	4	450/2320 mm	1600 mm	1230 mm

